

KABU

Upto
10 Years*
Warranty

HYDROPHOBIC WATERPROOFING

**International technology
Made in India, to Build India.**

**Nano technology
with hydrophobic
waterproofing treatment.**

Application areas

External / Internal Plaster, Stone Facade
Red Agra, Dholpur Stone, Laterite, Mandan
Stone, Exposed Concrete Facade, Brick
Facade, etc. To be used with KABU BOND
for superior results.

Mixing Ratio:

KABU LOCKSIL 1 Part :
KABU BOND 2 Part :
Clean Water 20 Part.

Note: Mixing ratio shall depend on application.




Available Packing
1Ltr, 5Ltr, 10 Ltr, 20 Ltr.

#ArtOfWaterproofing

www.KABU.world

080 6218 0982



Mixing Advise as per different Usage	Coverage after Mixing Per Sqft Per Coat	No. of Coats Advised
As top coat / As Base coat / As decorative Coat		
1 Part LOCKSIL : 20 Parts of Water	600 to 700	1

**SUPER HYDROPHOBIC COATING
WITHOUT FILM FORMATION**

KABU LOCKSIL

Innovating Construction Chemicals

DESCRIPTION

KABU LOCK is a Water/Solvent-based Non-film forming coating for all round protection of porous Building Materials from Water Ingress. It combats water penetration, leaching, acid rain deterioration, harmful effects of humidity, efflorescence and provides protection against moss and fungal growth.

FEATURES & BENEFITS

- Excellent Water Repelling Properties
- Long Lasting > 5 years
- Prevents ingress of water borne chlorides and sulphates
- Doesn't block breathability
- No Peeling off or Erosion
- Prevents Efflorescence
- UV Resistant
- Invisible layer after drying
- Prevents growth of Moss



TECHNICAL INFORMATION

- | | |
|---------------------------|--------------------------|
| • Physical State | - Liquid |
| • Appearance | - Transparent |
| • Odour | - Nil |
| • Ph | - 5.0 +-0.5 |
| • Boiling Point | - 100 Deg. C |
| • Specific Gravity | - 1.0 +- 0.1 |
| • UV | - Resistant |
| • VOC | - < 2gms / ltr |

KABU LOCKSIL

Innovating Construction Chemicals

AREAS OF APPLICATION

- External / Internal Plaster
- Stone Facade
- Red Agra, Dholpur Stone
- Laterite, Mandan Stone
- Exposed Concrete Facade
- Brick Facade

METHOD OF APPLICATION

- Surface Preparation - Make surface clean of dust, dirt, oil and stains
- To remove Efflorescence, Fungus / Mold, use to clean the surface.
- Shake well before use and dilute ratio would be 1 part LOCKSIL : 20 part water
- Apply on dry surface till saturation
- Let the surface dry and cure up to 72 hrs

AVAILABLE PACKING

1LTR, 5 LTR, 10LTR, 20 LTR, 50 LTR



HEALTH & SAFETY MEASURES

- **Respiratory Protection** - Use under normal conditions with adequate ventilation, no special respiratory protection is required for water based version. For Solvent based version, apply in well ventilated areas
- **Hand protection** - Use latex gloves while application
- **Skin Protection** - No specific protection required
- **Eye protection** - Use protective eye gear while application
- If swallowed, contact your nearest doctor immediately.