

KABU

Upto
10 Years*
Warranty

CLEAR COAT WATERPROOFING for multiple surface

International technology
Made in India, to Build India.

Clear Coat with UV
protection for multiple
surface with waterproofing

Application areas

External / Internal Plaster, Stone Facade
Red Agra, Dholpur Stone, Laterite, Mandan
Stone, Exposed Concrete Facade, Brick
Facade, etc.

Mixing Ratio:

Direct Application

Note: Mixing ratio shall depend on application.



Available Packing
1Ltr, 5Ltr, 10 Ltr, 20 Ltr.

#ArtOfWaterproofing

www.KABU.world

080 6218 0982



Mixing Advise as per different Usage	Coverage after Mixing Per Sqft Per Coat	No. of Coats Advised
Direct Application : As Top Coat / Decorative Hydrophobic Coat	80 to 100	2



CLEAR COAT

TRANSPARENT WATERPROOFING

KABU CLEAR COAT

Innovating Construction Chemicals



DESCRIPTION

KABU Clear Coat is a unique Nanotechnology based Clear Top Coat which gives >5 years of High Surface Durability and cut down repetitive maintenance needs for various exposed stone structures and Facades. It has Hydrophobic properties and prevents Water and humidity ingress from damaging the substrate. It also helps prevent fungal and mold growth on the stone surface, prolonging the beautiful look.

FEATURES & BENEFITS

- Excellent adhesion to glazed, ceramic surfaces and china mosaic tiles.
- Crack bridging ability
- Good abrasion resistance and resistance to weathering and UV
- Provides glossy finish to china mosaic
- Clear Transparent coating
- Elastic
- Easy to apply
- Resistance to foot traffic
- Offers waterproofing properties
- **Hydrophobic, Nanostructured Coating**
- **Superior Nanopowered Barrier Protection**

TECHNICAL INFORMATION

• Salt Spray Test	- 1500 Hrs
• Contact Angle	- 100 to 105 degrees
• Hardness	- 2H Pass
• Abrasion Resistance	- 48 Mg
• Impact Resistance	- Pass
Flexibility	27 Joules
• Humidity,	
Moisture Resistance	- No Effect
• Chemical Resistance -	
1. Isopropyl Alcohol	-- No Effect
2. Xylene	-- No Effect
3. 10% Hydro Chloric Acid	-- No Effect
4. 10% Sulphuric Acid	-- No Effect
5. 10% Sodium Hydroxide	-- No Effect
Coverage	13-15 Sqm / Ltr
Pot Life	30 mins (@25 degrees C)
Touch Dry Time	3 hrs (@25 degrees C)
Full Cure	24 hrs (@25 degrees C)

KABU CLEAR COAT

Innovating Construction Chemicals



AREAS OF APPLICATION

- Terrace of Commercial Buildings/Offices
- Hospitals
- Shopping Malls
- Home
- Apartments
- Oil Storage Tanks
- Factories
- Syntex tanks / water tanks and pipe lines
- Any type of old or new sheets and RCC roofs

METHOD OF APPLICATION

On Newly Coated Surface -

Surface to be made rough with 600 grit sanding paper. On completely dry surface free of oil, grease and dust, KABU CLEAR COAT can be applied directly.

Old painted Surface -

Surface should be dry and completely free of dust, dirt, oil and grease. KABU CLEAR COAT to be directly applied.

Any other surface -

Surface should be dry and completely free of dust, dirt, oil and grease. KABU CLEAR COAT to be directly applied.

COVERAGE

The coverage depends on the type of the surface. First coat smooth surface 80 to 100 sqft & Second coat smooth surface 90 to 110 sqft.

STORAGE & SHELF LIFE

Shelf life is 12 months in unopened container. Store away from sunlight and preferably below 30°C. Storage should be frost protected. High humid climate can reduce its shelf life.

CLEANING

Tools: Clean all the tools immediately with water. Use of thinner may be necessary for dried up material.

Hands: Use a hand cleaner or water followed by soap.

HEALTH & SAFETY

As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles should be worn.

AVAILABLE PACKING

1KG, 5KG, 10KG, 20KG, 50KG, 200KG