

KABU CLEAR COAT

Clear coating
with UV protection

**FOR INTERIOR OR
EXTERIOR SURFACES**

Surfaces for Application

- Painted Walls (interior / exterior)
- Cementitious terrace
- Floor tiles
- Variety of Stones
- Any matt finish stones / tiles.
- Paver blocks
- etc.



How to apply ?



Packing Available in Liters

5 & 10

DESCRIPTION

KABU CLEAR COAT is a unique nanotechnology based Clear Top Coat which gives >5 years of High Surface Durability and cut down repetitive maintenance needs for various exposed stone structures and Facades. It has Hydrophobic properties and prevents Water and humidity ingress from damaging the substrate. It also helps prevent fungal and mold growth on the stone surface, prolonging the beautiful look

FEATURES & BENEFITS

- High Durability of more than 5 years
- Excellent weather resistance
- High Chemical and Corrosion Resistance with excellent Barrier Protection
- High transparent stability, excellent UV Stability
- Two Component Coating, Easy to Apply
- Improved Aesthetics of Coated surfaces
- Excellent Waterproofing properties

TECHNICAL INFORMATION

- **Salt Spray Test** 1500 Hrs
- **Contact Angle** 100 to 105 degrees
- **Hardness** 2H Padd
- **Abrasion Resistance** 48 MG
- **Impact Resistance** Pass
- **Flexibility** 27 Joules
- **Humidity, Moisture Resistance** No Effect
- **Chemical Resistance -**
 - Isopropyl Alcohol** - -- No Effect
 - Xylene** -- No Effect
 - 10% Hydro Chloric Acid** -- No Effect
 - 10% Sulphuric Acid** -- No Effect
 - 10% Sodium Hydroxide** -- No Effect
- **Coverage** 13-15 Sqm / Ltr
- **Pot Life** 30 mins (@25 degrees C)
- **Touch Dry Time** 3 hrs (@25 degrees C)
- **Full Cure** 24 hrs (@25 degrees C)

AREAS OF APPLICATION

- Natural Stones
- Any type of Basalt, Sandstones
- Stone Facades
- Stone structures exposed to constant water spray.
- Masonry Architecture

METHOD OF APPLICATION

On Newly Coated Surface -

Surface to be made rough with 600 grit sanding paper. On completely dry surface free of oil, grease and dust, KABU CLEAR COAT can be applied directly.

Old painted Surface -

Surface should be dry and completely free of dust, dirt, oil and grease. KABU CLEAR COAT to be directly applied.

Any other surface -

Surface should be dry and completely free of dust, dirt, oil and grease. KABU CLEAR COAT to be directly applied.

STORAGE & SHELF LIFE

Shelf life is 12 months in unopened container. Store away from sunlight and preferably below 30°C. Storage should be frost protected.

CLEANING

Tools: Clean all the tools immediately with water. Use of thinner may be necessary for dried up material.

Hands: Use a hand cleaner or water followed by soap.

HEALTH & SAFETY

As with all chemicals, caution should always be exercised. Protective clothing such as gloves and goggles should be worn.

AVAILABLE PACKING

5 LTR, 10LTR, 20 LTR

KABU CLEAR COAT

Application for
CLEAR COAT
COATING on
MULTIPLE SURFACE



INTERIOR
Or
EXTERIOR

Can be applied on Tiles / China Chips / Concrete / Trimix / Paints / Marble / Black Stone / etc.

Application Details

Coating No.	No. of Coats	Mixing Ratio	Product	Apply with	General Terms 1.Surface preparation is mandatory for all application which includes smoothing the surface and filling all cracks by making a paste of KABU BOND + Water + Cement as required) 2.Warranty shall be applied on www.kabu.world warranty section)
2W	1 + 1	Direct Application	KABU CLEAR COAT	Brush / Roller	